

CMIP5672 H.264 IR Bullet IP Camera

Features

- 1/2.5" Progressive scan CMOS
- 2.8~12mm Varifocal Lens
- Dual Stream
- Up to 30fps @ 1920x1080 Res.
- 42 Pc IR LED
- BNC Out
- SD Card Slot- Support for MicroSD/HC, MiniSD/HC
- DC12V / PoE
- ONVIF Support w/ GeoVision v8.5



IP66

Specifications

Model	CMIP5672	
Image	Image Sensor	1/2.5" MT9P031 CMOS
	Image Frame Rate	1920x1080p @ 30fps
Electrical	Video System	NTSC
	Zoom	-
	Lens	f=2.8~12mm varifocal
	ICR	No
	Privacy Mask	-
	Video Output	1 BNC (PAL/NTSC, 1.0Vp-p, 75 Ω)
	White balance	-
	Video Scanning Type	-
	Sync. System	Internal
	S/N Ratio	> 48dB
Infrared	IR LEDs	42pc IR LEDs
	IR Effective Distance	-
	Smart control IR LED	-
Function	Video Compression	H.264/MJPEG
	Bit Stream Control	CBR, VBR
	Audio Input/Output	1 internal mic., 1 external mic, 1 Audio line out
	Audio Compression	G711/8KHz, G723.1/6.3kbps
	Audio Bit Stream	6.3Kbps
	OSD	Yes
	Audio and Video Sync	Yes
	Motion Detection	Yes
	Heartbeat	Yes
	Two-way voice talkback	Yes
	Alarm and Event Handling	Yes
	Network transmission control	Embedded network bandwidth adaptive flow control
	Network Protocol	IPv4/6, RTP/RTCP, TCP/UDP, HTTP, DHCP, DNS, FTP DDNS, PPPOE, SMTP
	Network Ethernet	RJ45, 10/100Base-T
	Alarm	1 Alarm Input, 1 Alarm Output
	RS485	Yes
SD Card	Support MicroSD/HC, MiniSD/HC	
Power	Input Voltage	9~12VDC +/- 5%
	Power Current	5W
Environment	Weather Protection	IP 66
	Operating Temperature	14°F ~ 122°F (-10°C ~ 50 °C)
	Storage Temperature	4°F ~ 144 °F (-20°C ~ 60 °C)
	Humidity	RH95% Max. (Non-condensing)
Mechanical	Chasis Material & Color	Metallic Dark Gray
	Product Dimension	240.00mm (w) x 85mm (h)

Dimensions

